remexit[®]

Sustainable construction alternative





> HIGH-QUALITY RECYCLED AGGREGATES

Solid basis with a seal of quality

remexit[®] is a quality-controlled recycled construction material produced in a variety of aggregates

mineral materials that result from the demolition, reconstruction or renovation of buildings or from

primarily for use in civil engineering, road construction and earthworks. Production is based on

Recycled aggregates are economical and sustainable alternatives to raw materials such as gravel and sand



High-quality construction material recycling

the expansion and maintenance of roads.

The processing of mineral construction waste from the construction and demolition of buildings and roads is carried out mechanically in the form of crushing, screening, sorting out impurities and separating iron. In order to achieve highest qualities, individual steps are carried out several times. The metals recovered in the process are recycled. The resulting mineral fraction is combined into different grain classes depending on the intended application.

Production locations

remexit[®] is a REMEX Group brand. The production and sale of recycled aggregates is carried out exclusively by REMEX or our subsidiaries and associated companies. You can find extensive details about our branded construction material, including a current list of our locations for the production of recycled aggregates, on the dedicated website > remexit.de

Applications made easy

The most important areas of application for remexit[®] in terms of volume are in road construction and earthworks. Due to its structural-physical properties, the recycled construction material is excellently suited for use as subbase and base course for roads of all load classes. Other important areas of application are industrial and commercial construction, where recycled aggregates offer ideal alternatives to primary aggregates due to their high load-bearing capacities. This is especially true in the logistics sector, where large loads have to be supported both from the substructure of warehouses and under transport surfaces with heavy traffic.

Environment defines the regulatory framework

The protection of soil and groundwater is an essential factor in the use of secondary construction materials such as recycled aggregates. Therefore, the local regulatory framework must always be observed before planning use. The most important influencing factors to be considered include the geographical location of construction projects within or outside water protection areas and the minimum distance of the material to the highest expected groundwater level.



Regulations at a glance

Numerous regulations must be observed for the recycling and reutilisation of mineral construction waste. These include detailed environmental specifications as well as comprehensive construction regulations. In principle, recycled aggregates are assigned to corresponding material or quality classes. The higher the quality, the more extensive the recycling options. An up-to-date overview of the relevant German publications for recycled construction materials can be found at > regulations.remexit.de You can find a summary of e.g. German application areas in relation to different material qualities at > **applications.remexit.de**



remexit[®] sets standards

Recycled aggregates consist mainly of concrete, clinker, asphalt, gravel and sand. The quality of the construction material is defined by the quality of input materials. Therefore, selective deconstruction and the separate collection and storage of mineral waste at the construction site are decisive aspects for ensuring high-quality construction material production. Within the framework of quality assurance, we apply a detailed control system.

| Recycling-optimised demolition | Project planner/owner | | Contaminated site? | |
|--|--|----------------|--|------|
| | | | SEPERATE COLLECTION | |
| | Contractor | | Selective dismantling | |
| - | | | INCOMING DELIVERY | |
| REMEX recycling plant | Internal production control/external quality control | | Data recordingRecognition of work regulationsVisual inspection at the scaleOrganoleptic controlRapid test tar etc. (optional)Assignment of input material to stockpileVisual inspection of stockpileSorting, preparationStorage of raw materialAssignment of quality class | |
| | | [1] | Documentation, weight note DELIVERY VCLED AGGREGATES | |
| Road construction, earthworks Civil engine | | Civil engineer | ing and building construction Other applications | 0 |
| quality. | .remexit.de | | _ 0 | NY J |

The suitability of recycled aggregates is determined within the framework of quality monitoring. This includes both material and water management testing. In Germany for example, only recognised test centres are permitted to carry out the proof of suitability testing and external monitoring. Corresponding test certificates serve as proof.

Environmental benefits of recycling

According to data from the German construction industry initiative "Kreislaufwirtschaft Bau", the German construction industry's demand for aggregates has averaged around 550 Mil. t in recent years. Around 12 % of this demand is covered by recycled aggregates. A relevant contribution to resource conservation – because every tonne that is not mined from natural ressources protects the landscape. At the same time, more than 200 Mil. t of mineral waste are produced in Germany every year in the form of soil, stones, construction and demolition waste and road rubble. The annual utilisation of about 70 Mil. t of this waste stream as recycled construction materials provides enormous relief to landfills.

Landscape protection

of **30 Mil. m³** gravel/sand pit volume or

³ un³ and 15 m excavation depth.

200 ha/a*

Relieving landfills of **70 Mil. t/a** of mineral waste

kreislaufwirtschaft-bau.de

Current data on the generation and utilisation of mineral construction waste in Germany can be found on the website of the industry association.

For calculation sources: see > sustainability.remex.de

remexit[®]

The REMEX Group combines special construction material solutions and service concepts for the waste management industry, construction sector and industrial production under the name REMEX Solutions. The portfolio includes secondary aggregates granova[®] and remexit[®] as well as the services pp.landfill for cooperation in landfill projects and ts.recycling for the management of road demolition waste containing tar.

T +49 211 17160-195

pp-landfill.de // ts-recycling.de

remex-solutions.de // granova.de // remexit.de